EV9613-01 MH Filter Cartridge		
	MH Replacement Cartridge: EV9613-01	<ul> <li>BENEFITS</li> <li>Provides clear, fresh, premium quality ingredient water for consistently great tasting coffee and beverages</li> <li>Everpure's unique filter blend using activated carbon reduces chlorine taste and odor and other offensive contaminants</li> <li>Saves energy by reducing scale build- up. Self-contained scale inhibitor feed dramatically prevents limescale from forming in brewing equipment</li> <li>Engineered to always feed the correct amount of scale inhibitor into each volume of water</li> <li>Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size</li> <li>Reduces health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts</li> <li>Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination</li> <li>NSF Certified under NSF/ANSI Standards 42 and 53</li> </ul>
INSTALLATION TIPS	OPERATION TIPS	A P P L I C A T I O N / S I Z I N G
Install vertically with cartridge hanging down Allow 2-1/2" clearance below the cartridge for easy cartridge replacement Flush cartridge by running water through filter for three minutes at full flow	Change cartridges on a regular 6 month preventative maintenance program Change cartridges when capacity is reached or when pressure falls below 10 psi Always flush the filter cartridge at time of installation and cartridge change	For coffee applications High flow, higher volume coffee urns Rated Capacity: 9,000 gallons (34,068L) or 18,000 pots

## MH Filter Cartridge

## S P E C I F I C A T I O N S

Overall Dimensions: 20.75"H x 3.25"Diameter

Service Flow Rate: Maximum 1.67 gpm (6.3 Lpm)

Rated Capacity: 9,000 gallons

Pressure Requirements: 10 - 125 psi (0.7 - 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

581815 18.75" WARRANTY System Tested and Certified by NSF International against NSF/ANSI Everpure water treatment systems (excluding replaceable elements) Standard 42 and 53 for the reduction of: are covered by a limited warranty against defects in material and Standard No. 42: Aesthetic Effects workmanship for a period of five years after date of purchase. Chemical Unit Everpure replaceable elements (filter cartridges and water treatment Taste and Odor Reduction cartridges) are covered by a limited warranty against defects in Chlorine Reduction material and workmanship for a period of one year after date of Mechanical Filtration Unit Particulate Reduction, Class I: purchase. See printed warranty for details. Everpure will provide a 99.9+% reduction of particles copy of the warranty upon request. one-half micron and larger in size Standard No. 53: Health Effects Mechanical Filtration Unit **Turbidity Reduction** Cvst Reduction Asbestos Reduction



EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe: N.V. EVERPURE (EUROPE) S.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals Belgium Tel 32 -14-283500 Fax 32-14-283505 In Japan: EVERPURE JAPAN LLC Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 Japan Tel 81-(0)42-775-3011 Fax 81-(0)42-775-3015

Everpure, LLC 1040 Muirfield Drive Hanover Park, IL 60133 Ph: 630-307-3000 Fax: 630-307-3030